



DESIGN NOTE:

- *STRUCTURE MUST SUPPORT 30 LB/SQ.FT SATURATED GSKY GREEN WALL SYSTEM
- *WALL SURFACE MUST BE SMOOTH
- *3/4" PLYWOOD MUST BE INSTALLED BEHIND GREEN WALL AREA
- *BLOCKING AT GSKY FRAME SCREW LOCATIONS MAY BE REQUIRED CHECK WITH PROJECT ENGINEER
- *STUD LOCATION MUST BE IDENTIFIED ON THE AS-BUILT DRAWING
- *GREEN WALL CAN BE RECESSED AT INDOOR WALL (NOTE THAT GUTTER WILL EXTEND OUT; SEE 8-p-1 FOR DETAIL)
- *WATERPROOFING IS REQUIRED TO BE APPLIED (LIQUID OR SELF ADHESIVE TYPE IS RECOMMENDED)
- *ADEQUATE LIGHTING MUST BE DESIGNED AND INSTALLED (FOR INTERIOR GREEN WALL)
- *WALL MUST BE ACCESSIBLE FOR MAINTENANCE (LIFT ACCESS MAY BE REQUIRED)
- *TRIM WIDTH MAY INCREASE DEPENDING ON LOCATION OF ZONE VALVES; SEE 9-p, 10-p AND 11-p FOR DETAIL
- *GREEN WALL BELOW MUST TO BE CLEAR FOR MAINTENANCE LIFT ACCESS

DRAWING TITLE:

GSKY GREEN WALL PANELS
FASTENER DETAIL / STUD WALL
 INTERIOR / EXTERIOR -
 WOOD OR METAL SCREW -



#704 - 318 HOMER ST
 VANCOUVER, BC V6B 2V2
 604-708-0611 ph 604-357-1315 fax
 www.g-sky.com

DATE: AUG 18, 2010
 REV DATE: N/A

SCALE: 3" = 1'-0"
 PAPER SIZE: 8.5 x 11

FILE #

3-p-4